

Vertical Baler V63XHD

This baler features a deep penetration 7" bore cylinder for producing high density bales of various OCC, plastics and metals.



We Design. We Manufacture.

800.728.1405 • www.cbebaler.com



Catawba Baler & Equipment, LLC

P.O. Box 20146 Greensboro, NC 27420 Phone: (336) 285-8592 • Fax: (336) 285-8595 www.cbebaler.com

(800) 728-1405

HEAVY DUTY VERTICAL BALER: V63XHD

This heavy-duty baler delivers greater compact force while still only taking minimal space. Designed for use in retail stores, manufacturing plants, warehouses, distribution centers or any location producing refuse paper, plastic and non-ferrous metals.

Specifications	
Performance	
Nominal Bale Size	60" x 30" x 48"
Bale Weight	Up to 1300 lbs OCC
Bale Volume	50 cu. ft.
No. of Bale Tie Slots	5
Compact Force lbs - Normal / Maximum	84,667 / 96,213
Average Cycle Time	67 Seconds
Loading Height	49.50"
Ejector System	Semi-Automatic
Full Bale Switch	Standard
Hydraulic / Electrical	
Motor HP	20
Voltage 3 Phase	208V, 230V, 480V
Full Load Amps (A = Amps)	59A, 54A, 27A
Pump GPM	15
Normal System Pressure PSI	2200
Max. System Pressure PSI	2500
Cylinder Bore x Stroke	7" x 60"
Hydraulic Tank-Capacity Gallons	30
ADDITIONAL HYDRAULIC/ELECTRICAL CONFIGURATIONS ARE AVAILABLE. PLEASE CALL CB&E FOR MORE INFORMATION.	

AVAILABLE OPTIONS:

- Slotted Front Door
- Wire Guides (allows for front bale tie-off)
- Rear Feed Opening, Front Eject
- Feed Chute
- Counter Weighted Floppy Retainer Dogs
- Oil Heater
- Weather Proof Package
- Full Bale Light

